

ASTERON

Panel Mount Printer 58 mm

NEW
Now available
12 + 24 V

KEY FEATURES

- Integrated paper bucket
- 2 versions : with or without embedded controller board
- Various fixing holes or integration by clip
- Enhanced design protects against spills & dust



Characteristics	Unit	Asteron 5V		Asteron 12/24V
Printing Speed (max)	mm/s			60
Paper Width	mm			58
Printing Width	mm			48
Resolution	dot/mm			8
Number of Dots				384
Paper Roll Diameter	mm			50
Paper Thickness	µm			60 - 80
Paper Loading	---			Clamshell™
Operating Voltage Range	VDC	4,5 - 8 V		10 - 36 V
Head Pulse Life	pulse			1*10 ⁸
Mechanical Life	km			50
Dimensions (W*D*H)	mm	With integrated board : 78 x 85,7 x 57 Without board : 78 x 77 x 57		
Weight	g	With integrated board : 104 g Without board : 88 g		
Operating Temperature	°C/F	0/50 - 32/122		
Cutting System	---			Manual tear bar
Interface	---			RS 232/TTL or USB 2.0
Sensors	---			Head temperature, paper end, cover open (micro switch)
Options	---			Available in charcoal or white casing

CONTROLLER BOARD

- Embedded controller board

