



Care.

Trust.

Responsibility.

PT-6215

All-In-One Point of Sale Terminal

Features At-A-Glance

Compact Fanless Design, Small Footprint

15" Touch Screen

Integrated MSR, Printer, Customer Display

Easy Cable Management



Specifications

Item	PT-6215
CPU	Intel Atom N270 @ 1.6 GHz / 512k L2 cache
Chipset	Intel 945 GSE + ICH7M
Memory	Standard DDR2 1GB, supports up to 2GB
LCD	15" TFT LCD
Resolution	1024 x 768
Touch	5-wire Resistive touch
LCD Brightness	250 nit (w/o touch)
LAN	10/100/1000 Mbps onboard Ethernet controller
Storage	SATA 3.5" hard drive or optional SATA SSD
I/O Ports	4 x COM ports 1 x RJ11 port (+24v) 1 x PS2 Keyboard port 1 x RJ-45 LAN port 5 x USB ports 1 x DC +12V 1 x VGA port
OS	POSReady / Windows XP Pro / Windows XP Embedded
Adaptor	AC 100V ~ 240V / DC12V power adaptor
Operating Temperature	32° F ~ 104° F
Storage Temperature	-4° F ~ 140° F
Operating Humidity	15% ~ 80%
Storage Humidity	15% ~ 80%
Dimensions	13.5" (W) x 12.6" (D) x 10" (H)
Integrated Peripherals	Triple track magnetic card reader 2" x 20" VFD customer display 3.14" Epson thermal receipt printer with auto cutter
Options	RFID module WIFI module

Features In Detail



www.partnertechcorp.com

Partner Tech USA • 51 Parker • Irvine • CA • 92618 • Tel: (949) 598-1888 • Fax: (949) 598-0088

© 2011 Partner Tech USA. All rights reserved.
Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All weights and measurements are approximate.