

CITIZEN

Compact. Connected. Complete.

Small size yet fully featured,
LAN-as-standard desktop printer



Compact

The small footprint of the new CL-E300CBI makes it a perfect printer for tight spaces but still allows labels up to 4.5 inches wide to be printed on a 5 inch media roll.

Connected

With an on-board Ethernet LAN interface as standard together with USB and Serial interfaces, the new healthcare CL-E300CBI is perfect for all applications. Citizen's LinkServer™ web management and configuration system is integrated to allow full printer control.

Complete

The CL-E300CBI has 203 and 300 dpi versions, as well as cutter and peeler options, allowing you to use it in every direct thermal application from low to mid volume printing.

CITIZEN CL-E300CBI

HEALTHCARE PRINTER

Healthcare Applications

- Patient Label
- Wristband
- Specimen Collection
- Pharmacy
- Labor & Delivery
- Laboratory

Complete peace of mind

The CL-E300CBI is simple to use and intuitive, ensuring users waste no time when changing labels or adjusting settings.



Energy efficient

Thanks to its Energy Star® compliant power supply, the CL-E300CBI series is one of the most environmentally friendly label printer ranges on the market.

CITIZEN

Well connected

Featuring on-board LAN, USB and Serial interfaces, the

CL-E300CBI series allows you to operate the printer remotely and adjust settings thanks to its LinkServer™ management tool which enables you to connect to the printers instantly via a web browser.



Specifications

| Model | CL-E300CBI Series |
|------------------------------|---|
| Printing technology | Direct Thermal |
| Resolution | 203 dpi and optional 300 dpi |
| Print Speed (maximum) | 8 inches per second (200 mm/s) at 203 dpi. 6 inches per second at 300 dpi |
| Print Width (maximum) | 4.1 inches (104 mm) |
| Media Width (min to max) | 0.94 inches to 4.65 inches (24 mm to 118 mm) |
| Media Thickness (min to max) | 63.5 µm – 190 µm, 0.0025 to 0.0075 inches |
| Media Sensor | Adjustable gap & black mark sensors |
| Media Length (min to max) | 6.4 – 2540 mm, 0.25 – 100 inches depending on emulation |
| Media Roll Size, Core Size | Up to 5 inches (125mm). Core 1 to 1.5 inches (25-38mm) |
| Standard interfaces | 10/100 Ethernet (LAN) with LinkServer™, USB 2.0, Serial RS232C |
| Case | Hi-Open™ plastic case with ClickClose™ Black and Pure White case colours |
| Control Panel | Feed/Setting button and two LEDs (Power & Status) |
| Memory configuration | 16MB Flash (User area 4MB), 32MB SDRAM (User area 4MB) |
| Drivers and software | Free-of-charge with printer, supporting Windows® 7, 8.1, 10, 2008R2, 2012, 2016, Linux and many others |
| Size (W x D x H) and Weight | 170 x 208 x 152 mm, 6.7 x 8.2 x 6.0 inches; 1.98 Kgs, 4.36 lbs. (AC adapter, 0.36 Kgs, 0.79 lbs) |
| Power consumption | 110 to 240 VAC (90 to 264 VAC), 50 to 60 Hz, 60W typical power consumption when printing DOE VI / COC Tier 2 compliant (less than 0.15W no-load consumption) |
| Printer, Head Warranty | 2 Years for Printer; 30 Kms/6 months on head |

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0



CITIZEN CL-E300CBI

HEALTHCARE PRINTER

Features & Benefits

- Ethernet LAN, USB & Serial as standard
- Small footprint and overall compact size to fit in the tightest of spaces
- Integral LinkServer™ web management enables easy operation and remote management of the printer
- Cross-Emulation™: Zebra® ZPL2 and Datamax® languages automatically selected and Citizen Basic Interpreter
- Tool-free maintenance for print head and platen
- Front access for all operations including media changing and sensor adjustment
- Adjustable media sensor as standard with label gap and black mark sensing
- Options include an autocutter and a pure white case, ideal for hospitals.

