

# CITIZEN

## The contemporary high-resolution label printer

Outstanding prints at 300 dpi



### Stylish, fast and compact

The CL-E331CBI's compact, modern, functional design takes up very little desk space, is easy to use and is also perfectly at home in any location, from warehouses to hospitals. It also has a fast print speed of 6 inches-per-second, is quick to setup and to load with media.

### Well connected

The CL-E331CBI features on-board LAN, USB and Serial interfaces. All industry-standard emulations are fully supported, with the option of remote operation via a web browser, using the Citizen LinkServer™ management tool.

### High quality printing in 300dpi

The CL-E331CBI the ideal choice for applications ranging from small test tube labels in healthcare to detailed rating plates in manufacturing. It is also equally suited to printing EAN barcodes and asset labels in the retail sector.

## CL-E331CBI

Label, Desktop

### Applications

- Manufacturing
- Healthcare
- Pharmacy
- Retail



Prints at a resolution of 300 dpi for when a clearer more detailed output is needed.

 **PERIPHERAL  
RESOURCES**

# CITIZEN



Ethernet LAN, USB and Serial interfaces as standard

## Specifications

|                                     |   |
|-------------------------------------|---|
| <b>Model</b>                        | <b>CL-E331CBI</b>   |
| <b>Printing Technology</b>          | Thermal Transfer + Direct Thermal   |
| <b>Resolution</b>                   | 300 dpi   |
| <b>Print Speed (maximum)</b>        | 6 inches per second (150 mm/s)  |
| <b>Print Width (maximum)</b>        | 4 inches (104 mm)   |
| <b>Media Width (min to max)</b>     | 1 to 4 inches (25 to 118 mm)  |
| <b>Roll Size (max), Core Size</b>   | Inside diameter 5 inches (125 mm) Core size 1 inch (25mm)   |
| <b>Media Thickness (min to max)</b> | 63.5 to 190 μm  |
| <b>Main Interface</b>               | Triple interface USB 2.0, RS-232 and 10/100 Ethernet  |
| <b>Mechanism</b>                    | Hi-Lift™ metal mechanism with wide opening head   |
| <b>Emulations (Languages)</b>       | Citizen Original Commands, Datamax® I-Class™ & DMX400™, Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400, Zebra® ZPL-II®, BASIC interpreter for data stream processing |
| <b>Size (W x D x H) and Weight</b>  | 178 x 266 x 173 mm, 2.6 Kg  |
| <b>Warranty</b>                     | 2 years manufacturer's warranty or 100 Kms on printer. 6 months or 50 Kms in TT mode or 30 Kms in DT mode on printhead  |
| <b>EMC and safety standards</b>     | CE, TUV, UL, FCC, VCCI  |

## CL-E331CBI

Label, Desktop

### Features & Benefits

- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- ENERGY STAR® compliant
- Small footprint



The CL-E331CBI has a wide opening 90° Hi-Lift™ case, and uses full size, 300m ribbons with standard 1 inch cores.

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

