CITIZEN

For your events - and for the environment

Energy efficient ticketing

Fanfold or roll media

The CL?S400DT can handle fanfold tickets as well as standard roll media for labels or receipts.

Easy read LCD panel

The LCD panel allows quick and simple configuration and also flashes red when an error occurs quickly alerting the operator.

Environmentally friendly

From production and packaging to utilization and recycling the CL-S400DT fulfills today‘s demand for green IT products. The integrated ENERGY STAR® power supply is one of the most efficient at managing power consumption.

TOMORROW'S PRINTING TODAY

Citizen Systems America Corporation, 363 Van Ness Way #404, Torrance, CA 90501, USA

CL-S400DT

Label, Ticketing

Applications

- Courier
- Retail
- Logistics / Transport
- Ticketing
- Kiosk
- Betting

Performance ticket and label printing

CITIZEN SYSTEMS AMERICA CORPORATION

CITIZEN

With a USB and serial interface on board the CT-S400DT is a future-proof investment. Ethernet and parallel interfaces are available as options.

Specifications

Model	CL-S400DT
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	6 inches per second (150 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	0.5 to 4 inches (12.5 to 118 mm)
Roll Size (max), Core Size	Inside diameter 5 inches (125 mm) External diameter 8 inches (200mm) Core size 1 inch (25mm)
Media Thickness (min to max)	63.5 to 254 µm
Media Length (min to max)	0.25 to 32 inches (6.35 to 812.8 mm)
Media Sensor	Fully adjustable gap, notch and reflective black mark
Main Interface	Dual Interface Serial (RS-232C), USB (version 2.0, full speed)
Interface	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT), Parallel (IEEE 1284 compliant)
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons, 16x2 LCD with 2-color backlight and sophisticated menu configuration system
Emulations (Languages)	Citizen Original Commands, Datamax® I-Class™ & DMX400™, Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400, Zebra® ZPL-II®, BASIC interpreter for data stream processing, EPL-2®
Drivers and software	Free-of-charge on CD with printer, including support for various platforms

Citizen Systems America Corporation, 363 Van Ness Way #404, Torrance, CA 90501, USA

CL-S400DT

Label, Ticketing

Features & Benefits

- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- Low space requirement - integrated power supply enables clean work station
- ENERGY STAR® compliant
- Small footprint
- Recyclable packaging
- Basic peeler

Compact footprint and metal mechanism

CITIZEN SYSTEMS AMERICA CORPORATION

CITIZEN

CL-S400DT

Label, Ticketing

Model	CL-S400DT
Flash (Non-Volatile Memory)	8 MB total, 1 MB available for user
Size (W x D x H) and Weight	206 x 149 x 150mm, 2.68 Kg (excluding roll holder)
Cutter	Guillotine type, Dealer Installable

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0