



SP-1000-C

High Powered POS Terminal

Features At-A-Glance

Intel Capella P4500, i5 or i7 CPU

Up To 8GB Cache Memory

Biometric Reader

Flexible Modular Design and Dual Display Support



Specifications

Item	SP-1000-C
CPU Type	Intel Capella P4500, i5 or i7
LCD	15" Active TFT color LCD, resolution 1024 x 768
Touch	5-wire Resistive touch (PS2 interface)
Memory	204pin DDR3 SO-DIMM 1GB (up to 8GB)
Ethernet	10/100M/1G
Storage	Internal 2.5" type SATA HDD 160GB x 2
I/O Interface	6 x COM ports (COM1~4 on rear I/O, COM5 Reserved, COM6 for VFD) 1 x DB-15 VGA port 1 x DB-25 for LPT port 1 x RJ-11 port for 2 cash drawers (+24V) 1 x RJ-45 LAN port with activity and link LEDs 2 x Audio ports (1 line out, 1 MIC in) 8 x USB 2.0 (4 on rear I/O, 1 for Mini-PCI-e, 1 for MSR+RFID reader, 2 reserved) 1 x DC +12V power adaptor connector
Expansion Options	1 x Mini PCI-e, supports Wi-Fi module
Optional Peripherals	3 track magnetic reader (Included) Customer display module (2x20 VFD) Biometric reader, Smart card reader, I-Button, RFID reader Dual screen 11.6" monitor
Operation System	Windows 7, Windows XP, XPe, Linux (ubuntu, Fedora), POSReady
Power Supply	AC100-240V/DC12V, 7.5A, 90 watt power adaptor
Dimensions	14.17" (W) x 9.84" (D) x 14.14" (H)
Operating Temperature	32° F ~ 104° F
Storage Temperature	-4° F ~ 140° F
Humidity	15% ~ 80%
Certifications	CE/FCC Class B, UL, cUL, CB, VCCI, BSMI

Features In Detail



1.8 GHz Dual Core Processor



Splash + Dust Resistant



Dual Display Support



Easy Access Hard Drive



Rear Customer Display



Custom Panel Color



Easy Access I/O Panel



Green Low Power Consumption



www.partnertechcorp.com

Partner Tech USA • 51 Parker • Irvine • CA • 92618 • Tel: (949) 598-1888 • Fax: (949) 598-0088

© 2011 Partner Tech USA. All rights reserved.
Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All weights and measurements are approximate.